Preliminary Amendment Attorney Docket Q67618

REMARKS

Entry and consideration of this Amendment is respectfully requested.

Respectfully submitted,

David J. Cushing

Registration No. 28,703

SUGHRUE MION, PLLC 2100 Pennsylvania Avenue, N.W. Washington, D.C. 20037-3213 Telephone: (202) 293-7060 Facsimile: (202) 293-7860

Date: December 12, 2001

10/009573 C13 Rec'd PCT/PTO 1 2 DEC 2001

Preliminary Amendment Attorney Docket Q67618

APPENDIX

VERSION WITH MARKINGS TO SHOW CHANGES MADE

IN THE CLAIMS:

The claims are amended as follows:

- 3. (Amended) An aircraft of the airplane or glider type according to claim 1-or elaim 2, characterized in that it includes at least one solar generator (5) cooled by convection with the surrounding air at said high altitude.
- 4. (Amended) An aircraft of the airplane or glider type according to any one of elaims 1 to 3 claim 1, characterized in that it includes at least one storage battery (7) having superconductive components.
- 5. (Amended) A method of getting an aircraft of the airplane or glider type as specified in any one of claims 1 to 4claim 1 onto station, the method being characterized by the following steps:
 - on the ground, said aircraft (1) is secured to an independent transporter (3);
- said transporter (3) takes said aircraft (1) to a high altitude at which it is to operate making use solely of propulsion means of said transporter (3);
- said transporter (3) releases said aircraft (1) at the altitude (H) and at least approximately at the intended location of its operating station; and
- if necessary, said aircraft (1) uses its own propulsion means (2) to put itself finally on station and take up its proper orientation.

Preliminary Amendment Attorney Docket Q67618

- 7. (Amended) A method of replacing a radio relay in a telecommunications network comprising a plurality of radio relays, the method being characterized in that said radio relay (10) is replaced by an aircraft (1) of the airplane or glider type as specified in any one of claims 1 to 4, claim 1, and provided with transceiver means (15) for radio waves (16, 17), said aircraft (1) being taken to an altitude and a position such that said transceiver means (15) lies in the same direction relative to at least one user (11, 12) of said telecommunications network (RT) as said replaced relay (10), with operation between said transceiver means (15) and said user (11, 12) being performed via an existing interface.
- 8. (Amended) A telecommunications network comprising a plurality of radio relays, characterized in that it includes at least one radio relay carried by an aircraft (1) of the airplane or glider type as specified in any one of claims 1 to 4claim 1, and put onto station at high altitude.